



US Patent #8,033,563

One Mount™ #10003 Instruction Sheet

Disclaimer: The ratings of the One Mount™ System are intended to represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. You, the consumer or operator, are strongly advised to learn the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

The One Mount™ System consists of two separate parts referred to as the Dual Flange Platform (DFP) and the Dual Flange Ball (DFB). The DFP (dual flange platform) is rated weight carrying up to 10,000 lbs. GVWR (gross vehicle weight rating) and up to 1,000 lbs. tongue weight.

The DFB (dual flange ball) is rated up to 10,000 lbs. GVWR/1000 lbs. tongue weight when using the 2-5/16" ball and 8,000 lbs. GVWR/800 lbs. tongue weight when using the 2" ball.

WARNING: Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever is less. See your Vehicle Owners Manual to determine Vehicle Tow Rating.

1. Install the platform into the 2" receiver hitch of your vehicle and secure it with the included silver hitch pin and clip. Always secure the hitch pin with a cotter pin unless a locking device is being used.
2. Determine which hitch ball size to be used is 2" or 2-5/16". Once the approximate height for the dual ball installation has been determined, mate the DFB (Dual Flange Ball) to the platform by inserting the supplied yellow pin through the hole that line up with the holes in the platform. Secure the pin with the included yellow clip.

Note: The supplied pins are specifically engineered for the One Mount™ System. If replacement pins are needed, they must be replaced with original factory One Mount™ pins.

WARNING: Use of any pin other than of One Mount™ manufacture could be a serious safety hazard and will void the warranty.

Notes:

- Prior to towing, check to make sure that the pins are secured into place with cotter pins.
- Never hook up trailer safety chains to the One Mount™ System.

Warning: Please ensure that the safety chains operate freely around the One Mount™ System and don't become entangled in the Platform or Dual Flange Ball.

