



INSTALLATION INSTRUCTION
INSTALLER: GIVE THIS INSTRUCTION TO VEHICLE OWNER

CLASS III TRAILER HITCH
P-100

5000 LB GROSS TRAILER WEIGHT
500 LB TONGUE WEIGHT

WARNING: CONSULT VEHICLE OWNERS MANUAL FOR TOWING RECOMMENDATIONS AND LIMITATIONS. THIS PRODUCT IS DESIGNED FOR TRAILER TOWING ONLY AND SHOULD NOT BE USED FOR ANY OTHER PURPOSE.

WARNING: DO NOT USE AS A WEIGHT DISTRIBUTING HITCH OR EXCEED YOUR VEHICLE'S TOWING CAPACITY OR BUMPER RATING.

NOTE: THIS HITCH IS DESIGNED TO FIT STEP BUMPERS WITH A FLAT CENTER PLATE WITH 8 TO 9 INCH HOLE CENTERS (OR MODELS THAT CAN BE DRILLED).

MOUNT THE HITCH TO THE VEHICLE AS FOLLOWS:

(A) USING THE 3/4" BOLTS PROVIDED, MOUNT THE HITCH PLATE TO THE BOTTOM LEDGE OF THE BUMPER CENTER PLATE USING THE EXISTING 3/4" OR 1" HOLES. ON MODELS THAT HAVE A LIP ON THE CENTER PLATE, USE THE 3/4" THICK SPACERS PROVIDED BETWEEN THE HITCH AND THE BUMPER. SOME MODELS WILL REQUIRE ONE 3/4" FLAT WASHER AS AN ADDITIONAL SPACER ON EACH BOLT. (FOR FORD FACTORY BUMPERS AND OTHERS WITH NO EXISTING HOLES, TWO 3/4" HOLES MUST BE DRILLED WHERE THE HITCH PLATE LINES UP CENTERED). MODELS WITH 1" HOLES REQUIRE TWO 3/4" FLAT WASHERS PROVIDED BE USED OVER THE HOLES.

NOTE: FOR SOLID FLAT PLATES THAT REQUIRE NO SPACERS, THE 3/4" BOLTS PROVIDED MAY BE REPLACED WITH SHORTER GRADE 5 BOLTS TO ELIMINATE EXCESS BOLT UNDER THE HITCH PLATE.

((B) MOUNT THE FRONT END OF THE HITCH PLATE BY DRILLING TWO 1/2" HOLES WHERE SPACE ALLOWS THE ATTACHMENT TO BE MADE. USE THE NECESSARY SPACER PLATES PROVIDED TO LEVEL THE HITCH. TWO OF THE 1/2" BOLTS WILL NOT BE USED, AND ALL SPACER PLATES MAY NOT BE REQUIRED TO COMPLETE THE INSTALLATION.

TIGHTEN ALL FASTENERS TO THE TORQUE SPECIFICATIONS SHOWN BELOW.

BOLT TIGHTENING TORQUE (LB-FT)

| BOLT SIZE | TORQUE | BOLT SIZE | TORQUE |
|-----------|-----------|-----------|----------|
| 3/8" | 25 LB FT | 8 MM | 20 LB FT |
| 7/16" | 50 LB FT | 10 MM | 38 LB FT |
| 1/2" | 60 LB FT | 12 MM | 68 LB FT |
| 3/4" | 120 LB FT | | |

THIS PRODUCT COMPLIES WITH SAFETY SPECIFICATIONS AND REQUIREMENTS FOR SAE AND VESC REGULATION V-5 FOR CONNECTING DEVICES AND TOWING SYSTEMS.
DO NOT MODIFY THIS PRODUCT. INSTALL ONLY ON SPECIFIED VEHICLES IN GOOD CONDITION.